95-PLATFORM



ROCK-SOLID STABILITY. MISSION-READY DESIGN.

E-ONE's 95-Platform has a proven reputation for durability and reliability. The welded extruded aluminum construction provides a low total cost of ownership. The bucket features angled corners and a perimeter step for excellent egress. Underneath the 95-Platform is the E-ONE exclusive integral torque box chassis for industry-leading strength and stability. The standard 245" wheelbase provides great maneuverability, and aerial setup is fast with its crisscross, underslung outriggers that have optional short jacking to allow operation in tight areas.

SOLID WORKHORSE.

The 95-Platform is a proven design that has stood the test of time for over 40 years and requires less space to set up than larger platforms. At 25% stronger, the 95-Platform exceeds NFPA requirements with a 2.5-to-1 structural safety factor.



SPECIFICATIONS

VERTICAL REACH	92'
HORIZONTAL REACH	82' 6"
OVERALL HEIGHT	11' 10" (+/-2"); 3" lower OAH available on some models using a trough cab
TIP LOAD	750 lbs. dry (500 lbs. wet) plus 275 lbs. equipment allowance
WATERWAY	Single monitor with up to 2,000 GPM flow
OUTRIGGERS	Crisscross, underslung with 13' 8" spread; auto level and short jacking with alley mode available
AERIAL CONTROLS	Advanced Aerial Control System (AACS) with variable speed control, body protection and color displays with mission-specific screens; wireless aerial controls optional
CAB	Typhoon® or Cyclone® cabs in 58" or 67.5" length; longer cabs available with truck company body
WHEELBASE	245" (250" with long cab, pump and tank)
CHASSIS FRAME	Integral torque box design combines the chassis frame and aerial torque box
ENGINE	Cummins® engines up to 605 HP
BODY CONFIGURATION	Extruded aluminum with full-height compartments each side; Quint with a pump, tank and hose bed or truck company style with no pump or tank; angled rear body corners and raised rear perimeter optional
GROUND LADDERS	Enclosed tunnel for Alco-Lite® or Duo-Safety® ladders; options for roof/wall ladders on aerial base and combo ladder on body
PUMP	Hale®, Waterous® or Darley® up to 2,000 GPM
TANK	300 gallons standard; 500 available



ANGLED CORNER PLATFORM
The bucket on the 95-Platform features angled front corners and perimeter step to provide easier egress. Its physical size is ideal for tight locations, with optional stokes receiver and parapet ladder brackets for enhanced rescue capabilities.



MORE STORAGE SPACE
What's a hardworking platform without plenty of storage? The 95-Platform is available with a SideStacker™ hose bed, 300-gallon tank, plus 182' of ground ladder storage.



INTEGRAL TORQUE BOX CHASSIS
The integral torque box chassis combines the chassis frame and aerial torque box into a single high-strength structure, providing a solid foundation for both the chassis and aerial operations.

E-ONE
DELIVERING STRENGTH THROUGH EXCELLENCE.

352.237.1122
info@e-one.com
Ver. 11.06.26
e-one.com

© 2026 Terex Corporation. All rights reserved.